

## Maximum permitted weights and dimensions, goods transport Norway

<b>Height</b>	no restriction *
<b>Width</b>	
Motor vehicle/trailer	2.55m
Refrigerated vehicle (minimum thickness of walls - 45mm)	2.60m
<b>Length</b>	
Motor vehicle	12.0m
Trailer	12.0m
Articulated vehicle	17.50m
Road train	19.50m
· with adjustable drawbar	19.50m
<b>Weight per axle on the main road network</b>	
single axle	10.0t
drive axle	11.5t
tandem drive axle**	19.0t
tandem axle, with a distance between the axles of	
· 1.20m - 1.29m	16.0t
· 1.30m - 1.80m	18.0t
· >1.80m	20.0t
tridem axle, with a distance between the axles of	
· 1.00m - 1.29m	22.0t
· 1.30m - 1.80m	24.0t
<b>Maximum permitted weight on the main road network</b>	
Motor vehicle	
· with 2 axles	19.0t
· with 3 axles	26.0t
· with 4 axles, and the distance between the first and last axle exceeds 5.8m, the distance between two neighbouring axles exceeds 1.8m in only one case, and with two drive axles	32.0t
Trailer	
· with 2 axles	20.0t
· with 3 axles	28.0t
· with 4 axles	30.0t
Semi trailer	
· with 2 axles	18.0t
· with 2 axles, if distance between the first axle and last steering axle exceeds 1.79m**	20.0t
· with 3 axles	24.0t
· with 3 axles, if distance between the first axle and last steering axle exceeds 1.79m**	27.0t
Road train with 6 axles**	50.0t
Modular- and timber- road train with 7 axles**	60t

\* however, there are many low bridges and tunnels – see detailed map obtainable from the [Vegdirektoratet](http://vegdirktoratet.no)

\*\* more detailed rules apply

**Source:** NLF, April 2015